

# United States Patent [19]

Ota et al.

### **Patent Number:** [11]

6,081,491

**Date of Patent:** [45]

Jun. 27, 2000

### [54] OPTICAL DISK VIBRATION SENSING AND REPRODUCING DEVICE

[75] Inventors: Takumi Ota; Akihiro Kishishita;

Kivoshi Kodani: Masavuki Hayashida, all of Tottori, Japan

Assignees: Sanyo Electric Co., Ltd., Osaka-fu; [73]

Tottori Sanyo Electric Co., Ltd., Tottori-ken, both of Japan

[21] Appl. No.: 09/378,657

Aug. 20, 1999 [22] Filed:

### Related U.S. Application Data

Continuation of application No. 09/162,988, Sep. 29, 1998, Pat. No. 6,009,053, which is a continuation of application No. 08/855,252, May 13, 1997, Pat. No. 5,886,966. [63]

[30]	For	eign A	pplicat	ion Priority Data
				G11B 3/90
[52]	U.S. Cl.		••••••	

369/48, 50, 53, 54, 58, 44.27, 44.28, 44.29, 44.32; 360/73.03

### [56] References Cited U.S. PATENT DOCUMENTS

, ,		Hoshino et al Syracuse .	
5,434,829	7/1995	Maeda et al 36	9/54 X
5,636,193 5,706,265		Bang 36	9/47 X

### FOREIGN PATENT DOCUMENTS

07182796 7/1995 Japan.

Primary Examiner-Paul W. Huber Attorney, Agent, or Firm-Akin, Gump, Strauss, Hauer & Feld, L.L.P.

#### **ABSTRACT** [57]

In an optical disk reproducing device capable of rotating an optical disk at a selected one of a plurality of preset linear velocities, vibration or shock of the device is detected during rotation of the disk, and the linear velocity of the disk is determined based on the result of the detection of the vibration or shock to restrain the vibration and shock within a permissible range. A limit rotational velocity above which the vibration or shock is excessive may be determined during a test conducted each time a disk is inserted, and the linear velocity of the disk during reproduction may be determined such that the rotational velocity does not exceed the limit rotational velocity.

## 11 Claims, 3 Drawing Sheets

